

TR


CRB Prizmatik Kanal Tipi Radyal Fan

Genel Özellikler

- 12.000m³/h kapasiteye kadar üretimi yapılabilmektedir.
- Maksimum verimlilikte radyal geri eğik kanatlara sahiptir.
- Gövde galvaniz saçtan imal edilmiş ve kendinden flanşlıdır.
- IP 54 motor koruması mevcuttur.
- Tüm modellerde hız kontrolü yapılabilmektedir.
- +50°C sıcaklıkta daimi çalışmaya uygundur.

Kullanım Alanları

- Genel mahal havalandırmaları
- Filtre sistemi ile birlikte mutfak davlumbaz egzozları
- Ofis, restoran, garaj, depo ve atölye havalandırmaları



EN

CRB Centrifugal Rectangular Duct Type Fan

General Features

- It can be produced up to 12.000m³/h capacity.
- It has radial backward curved blades with maximum efficiency.
- The fan casing is made of galvanized sheet steel and it is self-flanged.
- IP 54 motor protection is available.
- Speed control can be done in all models.
- Suitable for continuously operation at +50°C.

Areas of Usage

- General area ventilation
- Kitchen hood exhausts with filter system
- Office, restaurant, garage, warehouse and workshop ventilation



Genel Özellikler / General Features

MODEL	m ³ /h	V-50Hz	MOTOR			Statik Basınç Performans Tablosu (Pst/Pa)										SPL dB(A)
			(kW)	(rpm)	(A)	50	100	150	200	250	300	400	500	600	750	
CRB 400X200	1100	230V-50Hz	0,14	2600	0,60	1000	960	900	820	760	700	480				56
CRB 500X250	1450	230V-50Hz	0,20	2600	1,05	1400	1330	1220	1110	1010	900	600	300			57
CRB 500X300	1900	230V-50Hz	0,24	2500	1,10	1900	1880	1850	1800	1700	1550	1100	600			59
CRB 600X350	2550	230V-50Hz	0,21	1400	1,00	2400	2300	2000	1600	1300	1000					60
CRB 600X400	3300	230V-50Hz	0,40	1400	1,20	3100	2900	2700	2400	2000	1800	1300				62
CRB 700X400	4400	230V-50Hz	0,51	1380	1,50	4100	3900	3800	3500	3300	3100	2400	1800			66
CRB 700X500	5800	230V-50Hz	0,80	1350	2,50	5600	5300	5000	4600	4300	4000	3000	2000			68
CRB 800X600	9500	400V-50Hz	1,50	1400	2,60	9200	9000	8700	8300	8000	7500	6600	5400			76
CRB 1000X700	12000	400V-50Hz	2,50	1340	4,50	12000	11900	11800	11600	11400	11200	10400	9500	8200	6000	79

Ölçüler / Dimensions

MODEL	A	B	C	H
CRB 400X200	200	400	400	260
CRB 500X250	250	500	500	310
CRB 500X300	300	500	500	360
CRB 600X350	350	600	600	410
CRB 600X400	400	600	600	460
CRB 700X400	400	700	700	460
CRB 700X500	500	700	700	560
CRB 800X600	600	800	800	660
CRB 1000X700	700	1000	1000	760

